

SILENT CHECK VALVE (Globe Type)

消音止回阀

SPECIFICATION 规格

FLANGE TO BS EN1092-2 PN16/PN25

法兰规格符合BS EN1092-2 PN16/PN25

PRESSURE / TEMPERATURE RATINGS 压力/温度等级

Working Pressure 工作压力	16bar(DN50~DN600)	25bar(DN50~DN600)
Testing Pressure 测试压力	Shell (阀体) : 24 bar Seat (阀座) : 17.6 bar	Shell (阀体) : 37.5 bar Seat (阀座) : 27.5 bar
Working Temperature 工作温度	-10°C to 120°C	
Suitable Media 介质	Water & Oil 水/油	

MATERIALS 材质表

Part 部件	Material 材质	BS 英标
Body 阀体	Cast Iron 灰铸铁	1452 Gr.220
	Ductile Iron 球墨铸铁	2789 Gr.420/12
Disc 阀板	Ductile Iron 球墨铸铁	2789 Gr.420/12
	Stainless Steel 304 不锈钢304	BS970 304S15
	Stainless Steel 316 不锈钢316	BS970 316S16
Seat 阀座	Ductile Iron 球墨铸铁	2789 Gr.420/12
	Bronze 青铜	1400 LG2
	Stainless Steel 304 不锈钢304	BS970 304S15
	Stainless Steel 316 不锈钢316	BS970 316S16
Seat Ring 阀座密封圈	EPDM 乙丙橡胶	
Spring 弹簧	Stainless Steel 304 不锈钢304	BS970 304S15

DIMENSIONS 口径尺寸

Size [mm]	H [mm]
50	133
65	140
80	152
100	185
125	216
150	229
200	257
250	303
300	362
350	400
400	448
450	476
500	524
600	610

Note:

1. JIS B2239 10K, ASTM Class125, and other flange standards available upon request.
2. If used for gas application, please consult our sales office.
3. Design and specifications are subject to change without prior notice.

备注：

1. 可提供JIS B2239 10K,ASTM Class125及其他法兰连接标准的产品。
2. 如应用于气体，请联系我司确认。
3. 设计和规格如有修改，恕不另行事先通知。

GSCV-FB

PN16

PN25

DN50~600

