



SIZE	ØAL (mm.)	Min. Bending radius (mm.)	Max. Working Pressure (Bar@20Deg.C)	Max. Working Temp. (Deg.C)	Lateral Movement (mm.)	H1 (mm.)	H2 (mm.)	(M) x 2 (mm.)	BSPT-THREAD
15A	300	200	16	250	62	37	27	74	1/2"
20A	300	200	16	250	62	44	33	74	3/4"
25A	300	200	16	250	55	53	41	86	1"
32A	300	250	16	250	41	62	50	94	1-1/4"
40A	300	250	16	250	40	72	56	99	1-1/2"
50A	300	350	16	250	25	86	69	110	2"

ITEM	PART NAME / DESCRIPTION	MATERIAL	REFERENCE	Q'TY
1	WIRE BRAID	SUS304		1
2	SPIRAL HOSE	SUS304		1
3	LAP RING	SS 400		2
4	COLLAR	SS 400		2
5	UNION GASKET	NON ASBESTOS		2
6	UNION NUT	FCMB		2
7	UNION END	FCMB		2

PROPRIETARY DATA
THIS DOCUMENT CONTAINS TOZEN INDUSTRIAL CO.,LTD. CONFIDENTIAL INFORMATION AND SHOULD NOT BE USED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN PERMISSION OF TOZEN INDUSTRIAL CO.,LTD.

TOZEN INDUSTRIAL CO.,LTD.
3388/62 18th Fl. Sirinrat Bldg, PHONE: 0-2367-5721-8
Rama IV Rd., Klongtoey, FAX: 0-2367-5729
Bangkok 10110 0-2367-5066
WEBSITE: WWW.TOZEN.CO.TH

TITLE:
SF100 NW

MANUFACTURING TOLERANCES (UNLESS SPECIFIED OTHERWISE) TOLERANCES TO BE NON-CUMULATIVE					
LINEAR		ANGULAR	ROUNDNESS (CIRCULARITY)	CYLINDRICITY	
0 - 50 mm (INCL) ± 0.2 mm	50 - 500 mm (INCL) ± 0.5 mm	OVER 500 mm (INCL) ± 1 mm	±1°	± 0.5 mm	± 0.5%
NAME	SIGNATURE	DATE			
DRAWN			MATERIAL: -		
CHK'D					
APPV'D					
MFG					
Q.A					
DWG. NO. -				A4	
SCALE: 1:2				UNIT : mm	
				REVISION : 00	