

## STAINLESS STEEL Y TYPE STRAINER

### SPECIFICATION

BOLTED COVER  
STAINLESS STEEL PERFORATED SCREEN  
FLANGED TO BS4504 PN16

### PRESSURE / TEMPERATURE RATINGS

Working Pressure	16 bar
Testing Pressure	24 bar Hydrostatic
Working Temperature	Max. 120 deg.C
Suitable Media	Water & Oil

### MATERIALS

Part	Material
Body	Stainless Steel 304
Cover	Stainless Steel 304
Screen	Stainless Steel 304
Gasket	Resin
Drain Plug	Stainless Steel 304

### DIMENSIONS

Size		L		H	
mm	inch	mm	inch	mm	inch
50	2	220	8.7	130	5.1
65	2½	250	9.8	130	5.1
80	3	280	11.0	165	6.5
100	4	320	12.6	195	7.7
125	5	350	13.8	230	9.1
150	6	380	15.0	300	11.8
200	8	470	18.5	335	13.2
250	10	570	22.4	370	14.6
300	12	620	24.4	440	17.3

Note:

1. Other flange standards are available upon request.
2. If used for gas application, please consult our sales office.
3. Design and specifications are subject to change without prior notice.

**SYS-B**

**PN16**

